

Sea7[®]

PROVIEW[®]



Paani ki shwach boond..Pohanchaye har ghar..

**POWERFUL & ELEGANT
WATER PUMPS**



5 YEARS TRUST



For Trade Enquiry : +91 93870 95994

OPENWELL PUMP

OPW 50 PLUS / OPW 100 PLUS / OPW 150 PLUS / OPW 200 PLUS

POWER		PIPE SIZE (MM)	MODEL	TOTAL HEAD IN METER								
				8 M	10 M	13 M	16 M	18 M	25 M	28 M	32 M	40 M
KW	HP	SUC * DIS.		DISCHARGE IN LITRE PER HOUR								
0.50	0.5	25 * 25	OPW 50 PLUS	8000	6700	5800	4800	3000				
1.0	1.0	25 * 25	OPW 100 PLUS			9400	7000	4500	1400	300		
1.10	1.5	25 * 25	OPW 150 PLUS			11800	10500	8000	7500	5300	4000	
1.50	2.5	25 * 25	OPW 200 PLUS					12800	11200	8000	3500	2000

APPLICATIONS

- Pumping from domestic sump.
- Apartments, Hotels and other multistoried buildings,
- Quick filling of overhead tanks.
- Small Gardens, watering lawn etc.
- Watering Cattle fields.
- Fluid management from ponds, reservoir sand other water bodies.
- Seasonal Irrigations.

FEATURES

- Noiseless operation.
- Maintenance Free.
- Robust Water Lubricated Bush Bearings.
- Safest water resistant copper winding.
- Frame Material : Stainless Steel
- Motor: 2880 RPM CSR motor
- Insulation : Class "B"
- Bearing: LTB Bush Bearings
- Stampings: CRCA-Steel
- Oil Seal: Nitrile Rubber



JET PUMP

JET 100 (TWIN) / JET 200 (2"PKR)

POWER		PIPE SIZE (MM)	MIN. WELL SIZE (MM)	MODEL	TOTAL HEAD IN METER				
					9 M	12 M	18 M	24 M	30 M
KW	HP	SUC * PRES * DIS.			DISCHARGE IN LITRE PER HOUR				
0.75	1.0	32 * 25 * 25	100 MM	JET 100 (TWIN)	1800	1740	1450	1070	760
0.75	1.0	32 * 25 * 25	80 MM	JET 200 (2"PKR)	2100	2020	1320	640	250

APPLICATIONS

- Suitable for pumping water from sandy borewells.
- Residential Buildings, Bungalows, Lawn Sprinklers, Car Spa / washing,
- Well & Garages

FEATURES

- Careful Design and Rigid Construction
- Appropriate twin and packer type accessories.
- Noise free operation
- Trouble free operation for longer period
- High suction head
- Minimal mounting area requirement



ABOUT US

We deals in high quality products. We believe customers satisfaction is the first milestone in building the future roadmap of our company. Our objective & goal is to provide best goods at the best prices.

MISSION

Our aim is to create a niche for itself in the market of domestic & household products. We aim for that with the help of our dedicated team of professionals and with application of latest technologies, we could bring innovation in the productivity of our nation.

VISION

As a leading company, we are offering wide range of pumps to cater all your needs. Our products are durable, highly efficient, compactly designed, economical, highly operational and curated with high quality material

SELF PRIMING PUMP

Shyam 50 / Khatu 50 | Shyam 100 / Khatu 100 | Shyam 150 / Khatu 150 | Shyam 200 / Khatu 200

POWER		PIPE SIZE (MM)	MODEL	TOTAL HEAD IN METER										
				6 M	12 M	18 M	24 M	30 M	36 M	40 M	42 M	45 M	54 M	
KW	HP	SUC * DIS.		DISCHARGE IN LITRE PER HOUR										
0.37	0.5	25 * 25	Shyam 50 / Khatu 50	2800	2300	1900	1050							
0.75	1.0	25 * 25	Shyam 100 / Khatu 100	3300	2700	2200	1900	1500	1000					
1.1	1.5	25 * 25	Shyam 150 / Khatu 150	3800	3200	2700	2400	1900	1550	1200				
1.5	2.0	25 * 25	Shyam 200 / Khatu 200	4900	4200	3800	3200	2800		2200	1800		900	

APPLICATIONS

- Building curing purpose
- Domestic water lifting
- Small Lawn watering
- Faster filing of large over head tanks
- Suited for modern dwellings like Builders floors, Bungalows, hospitals, hotels, carwash, gardening
- Water transfer from underground sump to Overhead tank.

FEATURES

- Low voltage operating range from 150 volts.
- Light weight makes it easy to handle.
- Class-B insulation.
- High class Brass in panel for long life.
- Lower power consumption.
- Noiseless operation.
- Fitted with quality Thermal Overload Protector (TOP).
- Totally enclosed Fan Cooled (TEFC) Motor ensures better safety.
- Bearing: Double Shield Ball Bearing.
- High Quality Aluminium Body.
- Copper Winded.
- Back Pull Out for easy servicing.
- Longer working life.



Krishna 50 / Maruti 50 | Krishna 100 / Maruti 100 | Krishna 150 / Maruti 150

POWER		PIPE SIZE (MM)	MODEL	TOTAL HEAD IN METER							
				6 M	12 M	18 M	24 M	30 M	36 M	40 M	
KW	HP	SUC * DIS.		DISCHARGE IN LITRE PER HOUR							
0.37	0.5	25 * 25	Krishna 50 / Maruti 50	3100	2500	2100	1250				
0.75	1.0	25 * 25	Krishna 100 / Maruti 100	3600	3050	2500	2100	1800	1250		
1.1	1.5	25 * 25	Krishna 150 / Maruti 150	4200	3500	3200	2800	2200	1900	1450	

FEATURES

- Low voltage operating range from 180 volts.
- Light weight makes it easy to handle.
- Class-B insulation.
- High class Brass forged impeller for long life.
- Totally enclosed fan cooled (TEFC) motor ensure better safety.
- Double shield ball bearings provides noiseless & smooth running.



SHALLOW WELL PUMP

CSW 100 / RSW 100 | CSW 150 / RSW 150

POWER		PIPE SIZE (MM)	MODEL	TOTAL HEAD IN METER						
				6 M	12 M	18 M	24 M	30 M	36 M	40 M
KW	HP	SUC * DIS.		DISCHARGE IN LITRE PER HOUR						
0.75	1.0	25 * 25	CSW 100 / RSW 100	3300	3200	2900	2100	1200	900	
1.10	1.5	25 * 25	CSW 150 / RSW 150	3600	3400	3100	2700	1600	1300	800

FEATURES

- Wide Voltage operating range (180-240V)
- Specially designed for quick and powerful suction.
- No impeller jamming problem.
- Easy to install.
- Provision of rubber pad for shock absorption.
- Totally enclosed fan cooled (TEFC) motor ensure better safety.
- High quality die cast aluminium motor body and two tone color.
- Fitted with quality thermal Overload Protector (TOP)
- Capacitor start and run motor.
- Shaft - Stainless Steel.
- Special design protects motor against voltage fluctuation.
- Suitable for wide voltage variation.
- Copper Winded.



Sea7[®]

Follow us on:   

krishnaenterprises0019@gmail.com

PROVIEW[®]


KRISHNA ENTERPRISES